

www


KNOX

Organization Bldg./Room  
UNITED STATES PATENT AND TRADEMARK OFFICE

P.O. Box 1450  
Alexandria, VA. 22313-1450  
If Undeliverable Return In Ten Days

Official Business  
Penalty For Private Use, \$300

AN EQUAL OPPORTUNITY EMPLOYER



NIXIE 773 DE 1 00 10/13/09


RETURN TO SENDER  
NOT DELIVERABLE AS ADDRESSED  
UNABLE TO FORWARD

BC: 22319145050 \*0117-15176-90-41

770023555131301430



# UNITED STATES PATENT AND TRADEMARK OFFICE



UNITED STATES DEPARTMENT OF COMMERCE  
United States Patent and Trademark Office  
Address: COMMISSIONER FOR PATENTS  
P.O. Box 1450  
Alexandria, Virginia 22313-1450  
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
-----------------	-------------	----------------------	---------------------	------------------

10/815,130

03/31/2004

Norbert Steven Parsoneault

8209.053.NPUS01

9169

70165 7590 09/30/2009  
SEAGATE TECHNOLOGY LLC  
C/O NOVAK DRUCE & QUIGG LLP  
1000 LOUISIANA, Fifty-Third Floor  
HOUSTON, TX 77002

EXAMINER

KRAUSE, JUSTIN MITCHELL

ART UNIT

PAPER NUMBER

3656

MAIL DATE

DELIVERY MODE

09/30/2009

PAPER

**Please find below and/or attached an Office communication concerning this application or proceeding.**

The time period for reply, if any, is set in the attached communication.



Novak Druce & Quigg LLP

## facsimile transmittal

To: Examiner Krause

Fax: <sup>273</sup>571-~~272~~-3012

From: Michael Garrabrants

Date: 9/23/2009

Re: 10/815,130

Pages: 2 (including coversheet)

Cc: [Name]

RETURN FAX NUMBER: 415-814-6165

MY PHONE NUMBER: 415-814-6155

☐ Urgent ☐ For review ☐ Please comment ☐ Please reply ☐ Please recycle

**Notes:** Select this text and then delete it or replace with your own. To save changes to this template for future use, choose **Save As** from the **File** menu. In the **Save as type** list, click **Document Template**. The next time you want to use this template, choose **New** from the **File** menu, and then double-click the template.

Please see attached sheets

# confidential

Dear Examiner Krause:

Thank you for your proposed claim amendment. It does address your interpretation about the inner surface "having a hold formed there through" potentially still reading simply on the inner surface of the liner journal, with the second end hole. However, the claim doesn't leave adequate scope regarding certain embodiments. In particular, defining the surfaces as cylindrical and planar are too narrowing over the prior art, and exclude situations where there may be some tapering in a journal formed by such a liner, or something other than a completely flat liner bottom.

Would you consider a claim as proposed below? I believe that it addresses your concern, while not being unduly restrictive.

Thank you,  
Mike Garabrants

Current claim 1:

1. (Previously presented) A fluid dynamic bearing motor comprising:

- a base having a bore hole;
- a liner secured within the bore hole, wherein the liner includes a first end, and a second end, wherein the second end includes an inner surface having a hole formed there through;
- a rotor assembly having a shaft partially disposed within the liner, the shaft configured to rotate on the surface of the second end of the liner and relative to the liner;
- a fluid dynamic bearing disposed between the liner and shaft; and
- a recirculation channel disposed outside of the liner, the recirculation channel for recirculating lubricating fluid during relative rotation of the shaft and the liner.

Proposed Amended claim 1:

1. (Currently Amended) A fluid dynamic bearing motor comprising:

- a base having a bore hole;
- a liner secured within the bore hole, wherein the liner defines a journal including~~includes~~ a first end opening, and a second end distal the first end opening, the second end comprising a transverse surface ~~wherein the second end includes an inner surface~~ having a hole formed there through;
- a rotor assembly having a shaft partially disposed within the liner, the shaft configured to rotate on the transverse surface of the second end of the liner and relative to the liner;
- a fluid dynamic bearing disposed between the liner and shaft; and
- a recirculation channel disposed outside of the liner, the recirculation channel for recirculating lubricating fluid during relative rotation of the shaft and the liner.